


Nanoclass Square Pro Membrane TC

Product Range



Features



Applications



Filter Class



KEY FACTS

- High efficiency (H14 > 99.995 % at MPPS)
- Self-healing, fluid gel gasket
- Available in depths of 80 and 104 mm
- High tensile strength
- 100% boron free
- Minipleat technology for laminar flow
- Extremely low pressure drop
- Guaranteed leak free

DESIGN

e-PTFE membrane filter media folded into a pack and sealed into an anodized aluminum frame. A fluid gel gasket ensures a perfect seal between the filter assembly and its housing. Grid to front and rear faces.

APPLICATIONS

Final filter for clean rooms and clean workbenches. For separation of viruses, bacteria, toxic dust and aerosols, in hospitals/medical institutes, chemists, laboratories, clean rooms, pharmacy, food processing industry, microelectronics.

Nanoclass Square Pro Membrane TC

PERFORMANCE DATA

Article No.	Filter Class	Dimensions	Flow Rate	Pressure Drop
	EN 1822	mm	m³/h	Pa
800522024192	H14	305 x 305 x 104	150	55
800522024193	H14	305 x 610 x 104	300	55
800522024194	H14	305 x 762 x 104	375	55
800522024195	H14	305 x 915 x 104	450	55
800522024196	H14	457 x 457 x 104	350	55
800522024197	H14	457 x 610 x 104	450	55

Article No.	Filter Class	Dimensions	Flow Rate	Pressure Drop
	EN 1822	mm	m³/h	Pa
800522024198	H14	610 x 610 x 104	600	55
800522024199	H14	610 x 762 x 104	750	55
800522024200	H14	610 x 915 x 104	900	55
800522024202	H14	610 x 1220 x 104	1200	55
800522024203	H14	762 x 1220 x 104	1500	55
800522024204	H14	1220 x 1220 x 104	2400	55

SPECIFICATION

Recommended air flow	Flow rate \pm 10 %	Recommended final pressure drop	450 Pa (max. 600 Pa)
Heat resistance	Up to 70 °C (Peak 90 °C)	Moisture resistance	100 % rel. humidity
Regenerable	No	Incinerable	No

OPTIONS

Gasket	Self-healing fluid gel gasket
---------------	-------------------------------